

	DESIG	#	DRAWN BY	DART AEROSPACE HAWKESBURY, ONTARIO, CANAI	Maria (1990)
ı	CHECK	KED'W	APPROVED,/	DRAWING NO.	REV. A
ı		H	All	DSI 9270	SHEET 1 OF 1
ı	DATE			TITLE	SCALE
	03.1	03.12.02		REPLACEMENT SHIM KIT	NTS
	Α		03.12.02	NEW ISSUE	

## DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D412-698 REV. B
REF. CANADIAN STC: SH92-43

1) The D412-698-021 Replacement Shim Kit may be used to shim the D412-698-011/-012 Door Bracket Modification Kits in place of the existing Bell shims. Shim the door as specified in Installation Instructions IIN-D412-698 Rev. B. The kit includes the following parts:

QTY	P/N	Description	Used to shim bracket P/Ns:
Х	D412-698-021	Replacement Shim Kit	
3	D3238-1	Plate (replaces BHT P/N 205-031-436-003)	D3121-141/-145/-146
1	D3238-3	Plate (replaces BHT P/N 205-031-435-003)	D3121-143/-144
2	D3238-5	Plate (replaces BHT P/N 205-031-433-003)	D3137-043, D3183-043/-044
6	D3238-11	Plate	D3121-141/-145/-146
2	D3238-13	Plate	D3121-143/-144
4	D3238-15	Plate	D3137-043, D3183-043/-044

Use D3238-11 as required in conjunction with D3238-1.

Use D3238-13 as required in conjunction with D3238-3.

Use D3238-15 as required in conjunction with D3238-5.

2) To eliminate interference, it is acceptable to replace D3121-17 washer & MS24694S50 screw with D3121-21 bolt on all applicable bracket assemblies.

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-0-01

APPROVED

BY: D. SHEPHERD (DE # 02)

DATE: CERT. NO.: ISSUE NO.: 03.12.02 SH92-43 4